

High Brightness Sunlight Readable Behind Window Display



2500nits

SUNTRONIC
Outdoor LCD Signage

Model: W7500

Features Highlight:

- Perfect Application for Behind window displays
- 2500nits Bright Active Matrix TFT-LCD Display
- Stainless Steel Enclosures (Optional)
- WUXGA 1920 x 1080 Max. Resolution
- Digital or Analog Interface
- Super Wide Viewing Angles 178 deg (L/R)
- Auto Dimming
- Aspect Ratio: 16:9
- Multiple Video Input Selections
- Completely Sunlight Viewable
- Fast response time

Technical specifications

Module Size: 1,675.8(H) x 953.8(V)mm 82.8

Weight: 35,000g

Display Area: 1650.24 (H) x 928.26 (V)mm

Driver Element: a-Si TFT active matrix

Display Colors: 16.7m(8bit)

Number of Pixel: 1920 x 1080

Display Mode: Normally Black

Surface Treatment: Haze 0%

Luminance of White: 2500 cd/m²

Storage temp: -20 ~ 65°C

Operation temp: 0 ~ 50°C

Glass Surface temp (operation): 0 ~ 65°C

Storage humidity: 5 ~ 90 %RH

Operating humidity: 20 ~ 90%RH

Power Supply Voltage: 13.2V

Input Supply Voltage: 26V

Portrait Version: W7500P

Please contact SuntronicLCD for details

Available Accessories: IR Remote Control

Options: Custom Embedded PCs (please call for enquiries)

Customization: Please contact SuntronicLCD for available options

SUNTRONIC
Outdoor LCD Signage

EMAIL: sales@suntroniclcd.com • WEB: www.SuntronicLCD.com

