

57" Outdoor LCD GS5700L

i-Tech's All-Weather/Outdoor Full Sun environment Sunlight Readable LCD monitors allow you to view the display under the full sunlight. These affordable solutions are ready to deploy to any indoor and outdoor digital signage application for retail stores, restaurants, gas stations and many more....

We produce the largest and brightest Sunlight Readable LCD Monitor in sizes from 32" to 70".



Features Highlight:

- High-Brightness LCD Panel
- All Weather Proof IP65 Enclosures
- Operating Temperature -40C To 50C*
- Integrated heater and air conditioner
- Vandal Resistant Screen & housing
- Unique Front Access Design
- Remote Reboot/Temp.& Humidity Monitoring available (Optional)
- Wireless and VGA/DVI CAT5 signal extenders available (Optional)

Technical specifications

Active area size (W x H)	1251.36 x 703.89 (56.53")
Pixel pitch (mm)	0.21725 (H) x 0.65175 (V)
Panel resolution (pixels)	1920 x 1080
Luminance of white (Brightness)	1200 nits (Typ.) Max 2000nits
Contrast ratio	1500:1
Response time (gtg)	8 ms (Typ)
Colour Range	16.7 Million colours (max)
Viewing angle	89/89/89/89
Video inputs	VGA, HDMI, S-Video, Composite
Auto Brightness Control	Yes (Optional)
Front glass type	Strengthen 6mm AR glass
IP Class	IP65
Operating temperature range	-40 to + 100F(Direct Sunlight) /110F (Under Shaded Area)
Storage Temperature	0C to 50C
CCFL Life Time	60K hrs (min)
Input voltage	110V
Weight	350lbs
External dimensions (W x H x D)	1470W x 906H x 400D mm (58" x 35.7" x 15.8")

Portrait version	GS5700P, please contact SuntronicLCD for details
Available Accessories	IR Remote Control
Options	<ol style="list-style-type: none">1. Integrated CAT5/Fiber Optics VGA/DVI Extenders2. Custom Embedded PCs and Wireless3. Serial RS232 Input4. Screen Sensor/Environmental Sensors5. Auto Brightness Control Sensors
Customization	Integrated with Third Party Media player, please contact SuntronicLCD for available options

SUNTRONIC
Outdoor LCD Signage

