

Suntronic's Outdoor LCD Display

GS Series 65" LCD GS6500L1 Installed in Syracuse, NY 13204



Product Highlights:

- ▶ **Brightness: 1200 nits**
- ▶ **All Weather Proof IP65 Enclosures**
- ▶ **Operating Temperature -40C To 50C***
- ▶ **Integrated heater and air conditioner**
- ▶ **Vandal Resistant Screen & housing**
- ▶ **High-Brightness LCD Panel**

GS Series 55" LCD GS6500L1 Installed in Syracuse, NY 13204

Suntronic's All-Weather/Outdoor Full-Sun environment Sunlight Readable LCD monitors that allow you to view the display under the full sunlight. These affordable solutions are ready to deploy to any indoor and outdoor digital signage application for retail stores, restaurants, gas stations and many more...



Photos



Features Highlight:

- High-Brightness LCD Panel
- All Weather Proof IP65 Enclosures
- Operating Temperature -40C To 50C*
- Integrated heater and air conditioner
- Vandal Resistant Screen & housing
- Unique Front Access Design
- Build-in Monitoring Via RS232
- Optional Embedded PC or Media Player
- Optional Video Via CAT5 Extenders

Technical Specifications:

Display size (Diagonal) 64.5 inch

Brightness 1200nits (Typ)

Active area 1428.48 (H) x 803.52 (V)

Pixel pitch 0.744

Display Colors 1073.4M (10-bit)

Resolution 1920 x 1080

Viewing angle 89/89/89/89

Contrast Ratio 4000 : 1 (Typ)

Response Time 6.5ms

IP Class IP65/NEMA4

Video inputs HDMI, VGA

Input voltage 110V(GS6500L1) or 220V (GS6500L2)

Operating temperature range -40F to + 122F (Over 100F Not Recommended facing East/West Directly)**

Front glass type Anti Resistive Laminated glass

Portrait version GS6500P. Please contact SuntronicLCD for details
Weight 550 lbs (Est.)

External dimensions (62.7"W x 37.7" H x 15"D) (1592mmW x 957mmH x 377mm D)

Warranty One Year Standard Return to Depot Warranty (Optional 2 yr extended Warranty)