

High Brightness Sunlight Readable Behind Window Display with PC



Model: W4600HDL2

SUNTRONIC
Outdoor LCD Signage

FEATURES HIGHLIGHTS

- Perfect Application for Behind window displays
- 1500nits Bright Active Matrix TFT-LCD Display
- Stainless Steel Enclosures (Optional)
- 1920 x 1080 Max. Resolution
- Digital or Analog Interface
- Wide Viewing Angles 178 deg (L/R)
- Aspect Ratio: 16:9
- Multiple Video Input Selections
- Completely Sunlight Viewable

SPECIFICATIONS

Display Size: 46 Inch TFT-LCD
Resolution Capabilities: 1920 x 1080 Full HD
Frame Rate: 60Hz
Response Time: 8ms typical
Viewing Angle: 178°/178°
Contrast Ratio: 4000 :1
Brightness: **1500 cd/m², Completely Daylight Viewable**
Orientation: Landscape Mode
Backlight: 60,000 Hours Typical
Colors Supported: 10bit 1.07 Billion
Interface: VGA, HDMI , Min Display Port
Audio Out: 3.5mm Audio output
Speaker: Included 10Watts x 2
Power Source: 200-240VAC 50-60Hz
Power Consumption: 245Watts (with heater 345 Watts)
Temperature: **Operating: -15° to 60°C (5F to 140F)**
(Optional heater reach to -22F/-30C) Storage: -30° to 60°C
Humidity: Operating: 5 to 90% NC Storage: 5 to 95% NC
Operating Time 24/7/365
Dimensions: 46" (w) x 29" (h) x 7" (d)
Weight (Without Stand) 99lbs /45kg
RS232: Yes Control via command code
VESA Mount: 600 x 300/ 400

Auto Power On/Off: Yes
Auto Signal On/Off: Yes
Options: Wide Temp PC/ CAT5 Video Extender/portrait mode/Stainless steel Enclosures
Life time Life time 60K hours, operating Time 20 hours/Per day, Shock 30G / Anti Anti Shock 35G XYZ , Anti-Vibration 1G (10-300Hz)
Anti Shock/ Anti Vibration
Warranty: **Return to Depot Warranty1 year**

****Remarks: L for Landscape and P for portrait**

SUNTRONIC
Outdoor LCD Signage

EMAIL: sales@suntroniclcd.com • WEB: www.SuntronicLCD.com



Mechanical Drawing:

