Product Highlights:

- Brightness: 1200
- All Weather Proof IP65 Enclosures
- Operating Temperature -40C To 50C*
- Integrated heater and air conditioner
- Vandal Resistant Screen & housing
- High-Brightness LCD Panel

Installed at Sheraton Fairplex Hotel & Conference Center

Suntronic's All-Weather/Outdoor Full-Sun environment Sunlight Readable LCD monitors that allow you to view the display under the full sunlight. These affordable solutions are ready to deploy to any indoor and outdoor digital signage application for retails stores, restaurants, gas stations and many more...









Outdoor LCD Signage

Features Highlight:

- High-Brightness LCD Panel
- All Weather Proof IP65 Enclosures
- Operating Temperature -40C To 50C*
- Integrated heater and air conditioner
- Vandal Resistant Screen & housing
- Unique Front Access Design
- Remote Reboot/Temp.& Humidity Monitoring available (Optional)
- Wireless and VGA/DVI CAT5 signal extenders available (Optional)

Technical Specifications:

Active area size 55" (1387.80mm) diagonal

Outline Dimension 1286.0(H) \times 745.0(V) \times 60(D) mm (Typ.)

Pixel format (pixels) 1920(H) x 1080(V) (RGB stripes arrangement)

Color depth 10-bit , 1.07Billion colors

Luminance of white (Brightness) 1200 nits (Typ) at center 1 point

Contrast ratio 1600:1

Response time (gtg) 8 ms (Typ)

Colour Range 16.7 Million colours (max)

Viewing angle 89/89/89/89

Video inputs VGA; HDMI; S-Video

Auto Brightness Control Yes (Optional)

Front glass type Strengthen 6mm AR glass

IP Class IP6

Operating temperature range -40 to + 95F (Direct Sunlight) /122F (Under Shaded Area)

Storage Temperature 0 to 50C

CCFL Life Time 60K hrs (min)

Input voltage 110V

Weight 350lbs

External dimensions (W \times H \times D)

 $1470 \times 906 \times 463 \text{ mm} (58" \times 35.7" \times 18.2")$

Customization: Please contact SuntronicLCD for available options